

AIR LL20



Medium duty air hose for air drills and pneumatic tools, especially for mines, quarries and building.

TECHNICAL CHARACTERISTICS

TUBE	Black natural and synthetic rubber tube
REINFORCEMENT	High tensile textile
COVER	Black special rubber cover - abrasion - heat and weather resistant
OPERATING TEMP.	-30° C to +70° C
NORMS	-

CODE	Inner Diameter DN		Outside Diameter DN		Working Pressure		Burst Pressure		Theoretical Weight Kg/m
	mm	inch	mm	inch	bar	psi	bar	psi	
91A200613	6	1/4"	13	33/64"	20	290	60	870	0,160
91A200614	6	1/4"	14	9/16"	20	290	60	870	0,190
91A200816	8	5/16"	16	5/8"	20	290	60	870	0,220
91A200817	8	5/16"	17	43/64"	20	290	60	870	0,270
91A201018	10	3/8"	18	23/32"	20	290	60	870	0,260
91A201019	10	3/8"	19	3/4"	20	290	60	870	0,310
91A201322	13	1/2"	22	7/8"	20	290	60	870	0,370
91A201323	13	1/2"	23	29/32"	20	290	60	870	0,430
91A201625	16	5/8"	25	1"	20	290	60	870	0,440
91A201626	16	5/8"	26	1 1/32"	20	290	60	870	0,500
91A201929	19	3/4"	29	1 5/32"	20	290	60	870	0,570
91A201930	19	3/4"	30	1 3/16"	20	290	60	870	0,640
91A202536	25	1"	36	1 27/64"	20	290	60	870	0,790
91A202537	25	1"	37	1 15/32"	20	290	60	870	0,880