

LPG 25



LPG delivery hose
WP 25 bar

TECHNICAL CHARACTERISTICS

TUBE	GPL resistant black electrically conductive nitrile rubber tube;
REINFORCEMENT	High resistant textile reinforcement; Copper anti static wire.
COVER	Pin pricked rubber cover specially resistant to heat - abrasion and weathering; Smooth wrapped finish
TEMPERATURE	-30° C to +70° C
NORMS	EN 1762

CODE	Inner Diameter ID		Outside Diameter OD		Working Pressure		Burst Pressure		Theoretical Weight
	mm	inch	mm	inch	bar	psi	bar	psi	Kg/m
92GL25013023	13	1/2"	23	29/32"	25	363	100	1450	0,382
92GL25016026	16	5/8"	26	1 1/32"	25	363	100	1450	0,450
92GL25019031	19	3/4"	31	1 7/32"	25	363	100	1450	0,590
92GL25025038	25	1"	38	1 1/2"	25	363	100	1450	0,780
92GL25032045	32	1 1/4"	45	1 25/32"	25	363	100	1450	0,987
92GL25038052	38	1 1/2"	52	2 3/64"	25	363	100	1450	1,256
92GL25051067	51	2"	67	2 5/8"	25	363	100	1450	1,854
92GL25076094	76	3"	94	3 45/64"	25	363	100	1450	3,110
92GL25102120	102	4"	120	4 3/4"	25	363	100	1450	4,067